





# GDPF NBF



## Standard Temperature Data Logger -40 to +85°C



- + Collects and stores temperature information in the internal memory
- + Recover the data through the docking station using XpertLog Software
- + ITS-90 calibration coefficients are stored in the internal memory
- + Complies with FDA 21 CFR Part 11
- + Network ready: multiple users, centralized, server database, active directory authentication
- + Calibration can be performed on site



Sensor type	4 wires PT-100
- flexible	480 mm (19") PTFE/SS
- customized	Up to 5000 mm (195")
- sensor size	1.5 x 8 mm (0.06 x 0.315")
- cross section	1.77 mm <sup>2</sup> (0.0027 inch <sup>2</sup> )
Operating Range	
- body temp.	-40°C to +85°C
- sensor temp.	-40°C to +85°C
Accuracy	±0.1°C from -40°C to +85°C
Resolution	0.01 °C
Memory capacity	32,000 data points
Sampling rate	1 sec to 24 hours
Internal clock Drift	4 sec / 24 h @ + 23 °C
Mechanical	
- material	POM-C; FDA compliant
- enclosure	IP-67
- weight	44 g (1.55 oz)
- diameter	40.0 mm (1.57")
- height	50.0 mm (1.97")
Power	1 x Lithium battery, 0.35 g Lithium content classified UN3091 under IATA DGR section 3.9.2.6 compliant with ICAO/IATA packing instruction 970 user replaceable
Battery lifetime	Up to 12 months, based on usage
Docking station	USB to computer 4, 8, 12 and 20 ports available
Calibrations	Programs and reads unlimited number of loggers Factory: Traceable NIST / COFRAC - ITS-90 coefficients reside in the internal memory User: Closed loop user calibration, using XpertLog® Software
Certification	EMC: EN 60601-1-2 / 2007 Health & Safety: EN 60950-1/2006

Order Reference:

GDPF\_NBF

### Standard Calibration Points

- -40°C
- 0°C
- 85°C

